



ALL SEASON RETREADS

SPREAD AXLE (SA)

	WIDTH	NSD	Kg/Mtr	
	150	11.20	1.94	
	160	11.20	2.08	
	170	12.00	2.30	
	180	13.00	2.52	
	195	15.50	3.44	
	205	14.70	3.43	
	210	14.00	3.47	
	215	14.60	3.69	
	219	14.00	3.62	
	220	15.50	3.79	
	228	13.70	3.71	
	230	15.40	4.03	
	230	14.50	3.50	
	238	13.50	3.87	
	240	14.50	3.60	
	240	15.00	3.99	
	245	13.80	4.03	
	250	15.00	4.12	
	260	15.70	4.40	



HIGHWAY RADIAL (HWR)

	WIDTH	NSD	Kg/Mtr	
	205	12.50	3.08	
	220	13.00	3.53	
	228	13.00	3.66	
	238	13.50	3.97	
	240	12.75	3.74	
	250	14.50	4.48	



VAMSHI DRIVE MASTER (DM)

	WIDTH	NSD	Kg/Mtr	
	153	11.70	2.13	
	160 H	14.70	2.79	
	187	15.00	3.23	
	203	15.30	3.58	
	205	12.20	3.16	
	205	17.00	3.91	



VAMSHI RADIAL XPRESS (VRX)

	WIDTH	NSD	Kg/Mtr	
	205	13.20	3.02	
	215	13.00	3.35	
	220	13.80	3.43	



VAMSHI RADIAL EXCEL (VRE)

	WIDTH	NSD	Kg/Mtr	
	240	16.00	4.30	
	250	16.00	4.48	
	260	14.50	4.35	



APPLICATIONS

					
Highway	Regional	Urban	Mixed	Off Road	M+S

"± 2% Tolerance to be allowed"

Length of tread maximum up to 3750 mm can be supplied
Our Products are "REACH" Compliant

VAMSHI DRIVE HEAVY DUTY (VDHD)				DIRECTIONAL
				   
	WIDTH	NSD	Kg/Mtr	
	220	15.00	3.57	
	230	15.00	3.75	
	240	21.00	5.33	
	250	21.00	5.54	
	260	21.00	5.78	
270	21.00	6.03		




VAMSHI DRIVE SPECIAL (VDS)				DIRECTIONAL
	 WIDTH	 NSD	 Kg/Mtr	  
	220	15.75	3.70	
	230	16.00	3.94	
	240	17.00	4.41	
	240	15.00	3.85	
	250	17.00	4.50	
	260	17.00	4.70	




VAMSHI HEAVY HAUL TRACTION (VHHT)				DIRECTIONAL
				  
	WIDTH	NSD	Kg/Mtr	
	240-D	22.00	5.40	
	250-D	22.00	5.60	
260-D	22.00	5.84		



VAMSHI LONG HAUL DRIVE-DEEP (VLHD-D)				
				 
	WIDTH	NSD	Kg/Mtr	
	250-D	22.00	5.60	
	260-D	22.00	5.76	
	270-D	22.00	5.99	



VAMSHI DRIVE MIXED SERVICE (VDMS)				
				
	WIDTH	NSD	Kg/Mtr	
	240	18.20	4.70	
	250	18.50	5.00	
	260	18.60	5.20	
	270	18.50	5.40	



VAMSHI RADIAL TRACTION (VRT)				
				
	WIDTH	NSD	Kg/Mtr	
	160	15.00	2.70	
	180	16.00	2.80	
	190	16.00	3.00	
	230	20.00	4.88	
	240	18.00	4.61	
	250	18.00	4.78	
260	20.00	5.61		
270	20.00	5.18		



“± 2% Tolerance to be allowed”


Length of tread maximum up to 3750 mm can be supplied
Our Products are “REACH” Compliant

VAMSHI GRIP RDIAL - DEEP (UGR-D)

	WIDTH	NSD	Kg/Mtr	
	230-D	20.10	4.88	
	240-D	22.00	5.49	
	250-D	22.10	5.95	
	260-D	22.20	6.07	
	270-D	22.00	6.27	



VAMSHI CROSS COUNTRY DRIVE-DEEP (VCCD-D)

	WIDTH	NSD	Kg/Mtr	
	240	19.50	5.25	  
	250	19.20	5.29	
	260	19.20	5.55	



VAMSHI MULTI MILLER (VMM)

	WIDTH	NSD	Kg/Mtr	
	230	15.00	3.84	
	240	15.50	4.09	
	250	15.50	4.25	



VAMSHI MEGA TREK (VMT)

	WIDTH	NSD	Kg/Mtr	
	160	11.80	1.86	
	180	14.00	2.51	
	190	14.00	2.65	



VM + S4

	WIDTH	NSD	Kg/Mtr	
	150	12.00	1.80	
	160	12.00	2.00	
	180	14.00	2.48	
	190	14.50	2.65	
	200	16.00	3.04	



HEAVY RUG RADIAL (HLR)

	WIDTH	NSD	Kg/Mtr	
	187	14.40	3.08	
	205	14.00	3.44	
	210	14.00	3.49	
	215	13.90	3.54	
	220	13.80	3.62	
	220-H	18.00	4.59	



"± 2% Tolerance to be allowed"

Length of tread maximum up to 3750 mm can be supplied
Our Products are "REACH" Compliant

LUG TRAC (LT)

	WIDTH	NSD	Kg/Mtr	
	160	13.50	2.51	
	170	13.00	2.65	
	187	14.50	3.26	
	195	13.80	3.20	
	203	14.80	3.56	
	205	13.50	3.37	
	210	14.70	3.50	
	215	15.00	3.65	



WASTE HAULER LUG (WHL)

	WIDTH	NSD	Kg/Mtr	
	160	12.50	2.19	
	170	14.50	2.70	
	180	14.60	2.95	
	195	14.50	3.30	
	205	14.00	3.32	
	212	15.00	3.78	
	219	15.00	3.57	



HGC

	WIDTH	NSD	Kg/Mtr	
	205	15.50	3.57	
	210	15.00	3.57	
	215	15.00	3.64	
	219	14.00	3.63	
	228	12.80	3.68	



CROSS BAR (CB)

	WIDTH	NSD	Kg/Mtr	
	153	11.00	2.09	
	203	14.50	3.53	
	210	14.20	3.63	



VAMSHI RADIAL SUPER DRIVE (VRSD)

	WIDTH	NSD	Kg/Mtr	
	215	13.70	3.45	
	220	14.00	3.63	



ULTRA GRIP RADIAL (UGR)

	WIDTH	NSD	Kg/ Mtr	
	210	14.50	3.35	
	219	13.50	3.35	
	280	15.00	4.53	
	270	15.00	4.37	
	290	15.00	4.72	



VAMSHI SUPER MIXED SERVICE (VSMS)

	WIDTH	NSD	Kg/Mtr	
	240	20.50	5.10	
	250	20.50	5.30	
	260	20.50	5.50	



"± 2% Tolerance to be allowed"

Length of tread maximum up to 3750 mm can be supplied
Our Products are "REACH" Compliant

VAMSHI TRAILER PLUS -WING (VTP-W)

	WIDTH	NSD	Kg/ Mtr	
	290	14.20	5.09	
	305	13.00	4.87	



VAMSHI SUPER HAUL TRAILER-WING (VSHT-W)

	WIDTH	NSD	Kg/ Mtr	
	295	14.50	4.75	



VAMSHI TRAILER SPECIAL WING (VTS-W)

	WIDTH	NSD	Kg/ Mtr	
	295	13.00	4.40	



VAMSHI TRAILER SPECIAL (VTS)

	WIDTH	NSD	Kg/ Mtr	
	290	14.00	4.60	
	300	14.00	4.88	
	310	14.00	4.90	
	320	14.00	5.10	



MINES EXCLUSIVE (MEX)

	WIDTH	NSD	Kg/ Mtr	
	205	13.20	3.33	



SUPER LUG MINES (SLM)

	WIDTH	NSD	Kg/ Mtr	
	240	18.50	4.89	



MINES TRACK (MT)

	WIDTH	NSD	Kg/Mtr	
	205	13.80	3.33	
	240	15.00	4.31	
	240	19.20	4.95	
	310	25.00	9.15	



VAMSHI ROCK LUG- DEEP (VRL-D)

	WIDTH	NSD	Kg/ Mtr	
	240	22.00	5.81	



MINES TRAC DEEP (MTD)

	WIDTH	NSD	Kg/ Mtr	
	240	19.20	4.95	



"± 2% Tolerance to be allowed"

Length of tread maximum up to 3750 mm can be supplied
Our Products are "REACH" Compliant

OTHER PRODUCTS

BONDING GUM



VULCANISING SOLUTION



EXTRUDED ROPE RUBBER



RUBBER COMPOUND SHEET



* Width upto 480 mm can be supplied
* required thickness can be supplied



One of India's leading manufacturers of a comprehensive range of retread material, retreading equipment, tools and all other allied products essential in the tire retreading industry.

Tested & Trusted for:

- **Durability**- cooler running optimum tread design.
- **Economy**- low rolling resistance compounds for greater mileage.
- **Safety**- Tread design suited for higher traction & better grip.
- **Longer Life**- Specific compounds for abrasion resistance to enhance casing & tread life.
- **Eco-Friendly**- Manufacturing process confirms to global procedures of Reduce- Reuse--Recycle.



CORP OFFICE:
Vamshi Rubber limited
Vamshi House Plot No:41,
Jayabheri Enclave , Gachibowli
Hyderabad -500 032.

Mobile :+91 99894 88153
Email: info@vamshirubber.org